



## LockMaster™

Generated on 01.11.2018

### Detailed description

LockMaster™ gates are of welded SHS construction, with the rigid mesh panels fixed by standard clamp bar and through fixings. All hinges are anti lift-off and adjustable, the gates back-hung and fitted with the LockMaster™-type locking mechanism, an integral swing bolt lockcase complete with a eurocylinder eliminating footholds and providing a facility that can be suited with most modern door lock systems or one of the many lock arrangements from the CLD range. The gates are supplied with steel drop bolt sockets to be set in concrete. The drop bolts are lockable in both closed and open positions. A variety of toppings are available for the range of gates, including standard barbed wire or razor wire, or more sophisticated toppings such as anti-climb rotating spike or saw-tooth edge.

### Features:

- Double or single leaf opening.
- Matching infill options.
- Lockable drop bolts.
- Secure design.
- Automation option.

### Applications:

- Parks.
- Schools.
- Amenity areas.
- Industrial applications.

### Product guidance - As Standard

#### Posts:

80 x 80 x 4 to 250 x 250 x 6.3 mm SHS, depending on gate height.

#### Options

##### Gate size:

##### - Height:

400–3800 mm as standard - other heights are available on request.

##### - Width:

- Single: 0.6–7.0 m.
- Double: 1.2–14.0 m.
- All gates made to client specification.



**CLD Fencing Systems**  
Unit 11  
Springvale Business Centre  
Millbuck Way  
Sandbach  
Cheshire  
CW11 3HY

Tel: +44 (0)1270 764751

[www.cld-fencing.com](http://www.cld-fencing.com)  
[sales@cld-fencing.com](mailto:sales@cld-fencing.com)



### Mesh:

Insert panel system required to match.

### Colour and finish:

Polyester powder-coated green RAL 6005 as standard. Full spectrum of colours available subject to quantity and price.

### Locking mechanism:

A large and varied range of access control options are additionally available to complement the range of fence systems and gates. Contact manufacturer for details.

## Product specification

### Manufacturer

- Name: CLD Fencing Systems
- Web: [www.cld-fencing.com](http://www.cld-fencing.com)
- Email: [sales@cld-fencing.com](mailto:sales@cld-fencing.com)
- Tel: +44 (0)1270 764751
- Fax: +44 (0)1270 757503
- Address: Unit 11, Springvale Business Centre, Millbuck Way, Sandbach, Cheshire CW11 3HY

<b>Product reference</b>	LockMaster™ - Swing gates.
<b>Type</b>	Double Single
<b>Height</b>	400 mm 600 mm 1200 mm 1400 mm 1800 mm 2000 mm 2400 mm 3000 mm 3800 mm
<b>Hinges</b>	Left hand hung Right hand hung
<b>Gate width</b>	[ _____ ]
<b>Mesh</b>	Dulok Dulok 25 Dulok lite Dulok rebound Eclipse Exempla Multiplus



	Securus flat Ultimate Ultimate extra Vertical bar
<b>Colour and finish</b>	Galvanized and polyester powder coated, RAL - Full RAL range of colours available.
<b>Locking mechanism</b>	CodeLock Fire exit panic latch LockMaster slide bar LockMaster cylinder
<b>Anti-intruder security topping</b>	None Anti-climb rotating spike Barbed wire Razor wire, coiled Saw-tooth edge