



SlideMaster™

Generated on 06.11.2018

Detailed description

The SlideMaster™ cantilevered and tracked sliding gates are made to order and can be supplied with a height of up to 3 m with a drive through width of up to 20 m, all with 125 mm ground clearance. The main gate frame consists of upper and lower 75 mm square aluminium tube rails with the main uprights made from the same material. The gates can be infilled with any of the mesh panels from the CLD range or can have a standard 30 mm round bar infill at 125 mm centres – the frame and infill is then mounted on our custom made lower beam extrusion. The SlideMaster™ cantilever drive mechanism is unique in that the external friction drive is incorporated in the lower beam as opposed to the inside face of the gate therefore protecting it from the elements as well as being completely out of view. The automated SlideMaster™ cantilevered sliding gates are fully compliant with the EU standard BS EN 12453, having five profiled safety edges each consisting of two parallel electrically conducted rubber strips. These are connected to the main control panel by two cables, which are concealed within the lower beam, which transmit messages to and from the safety edges. In the unlikely event of a fault, messages will be transmitted to the necessary safety edges instructing the gate to be stopped regardless of its position.

Features:

- Ideal solution for large openings.
- Clear drive through widths up to 20 m.
- Full range of panel infills.
- Full range of RAL colours.

Applications:

- Industrial and retail parks.
- Data centres.
- Airports and seaports.
- Ministry of Defence (MOD).
- Schools, colleges and universities.

Product guidance - As Standard

Frame:

75 x 75 mm aluminium tube.

Options

Size:

- Height: Up to 3 m.
- Width: Single: 1.2–10 m, double: 2.4–20 m. All gates made to client specification.

CLD Fencing Systems



CLD Fencing Systems
Unit 11
Springvale Business Centre
Millbuck Way
Sandbach
Cheshire
CW11 3HY

Tel: +44 (0)1270 764751

www.cld-fencing.com
sales@cld-fencing.com



Locking mechanism:

A large and varied range of access control options are additionally available to complement the range of fence systems and gates. Contact manufacturer for details.

Product specification

Manufacturer

- Name: CLD Fencing Systems
- Web: www.cld-fencing.com
- Email: sales@cld-fencing.com
- Tel: +44 (0)1270 764751
- Fax: +44 (0)1270 757503
- Address: Unit 11, Springvale Business Centre, Millbuck Way, Sandbach, Cheshire CW11 3HY

Product reference	SlideMaster™ Cantilever Sliding Gate Slidemaster SR1 Slidemaster SR2 Slidemaster SR3
Operation	Automatic Manual
Height	1200 mm 1800 mm 2000 mm 2400 mm 3000 mm
Size (h x w)	[]
Infill	30 mm round bar - 125 mm centres. 30 mm square bar - 125 mm centres. Exempla mesh Dulok mesh Multiplus mesh
Infill	Mesh - Insert panel system required to match. See options. 30 mm round bar - 125 mm centres. 30 mm square bar Securus Ultimate mesh Ultimate extra
Colour and finish	Powder coated, RAL - Full RAL range of colours available.
Locking mechanism	Not required SlideLock



ribproductselector.com

A building products library for construction industry professionals

NBS Plus